METCLEAN

OFF-VEHICLE

INSTRUCTIONS

DPF ONE SHOT

Cleaning removed DPFs on the METclean Lite, or as a pre-soak before finishing on a METclean machine.

METCLEAN DPF ONE SHOT

METclean DPF One Shot is a single stage, water based and non-flammable DPF cleaner. For off-vehicle cleaning it breaks down soot and oil residues inside the honeycomb structure of a removed diesel particulate filter.

Use it in one of two ways: **Option A** as a wash additive in the METclean Lite, or **Option B** as a one hour direct soak before finishing the clean on a METclean machine.

1L	**500ml**	**1 HR**	**2**
Per 25L METclean Lite tank	Per DPF for a direct soak	Direct soak time	Direct soaks from every 1L bottle

YOU WILL NEED

- METclean DPF One Shot, 1L bottle
- METclean Lite (Option A)
- Drip tray and sealed waste container
- Clean water
- Blanking plugs or caps for the DPF (Option B)
- Chemical resistant gloves and goggles

BEFORE YOU START



DANGER

H315 Causes skin irritation.
H318 Causes serious eye damage.
Alkaline (pH 11.3). Work in a well ventilated area and do not breathe vapour or spray. Do not eat or drink while using.

GLOVES | GOGGLES | VENTILATION

OPTION A: METCLEAN LITE

1. Fill the METclean Lite tank with **25L of clean water**.
2. Add **one full 1L bottle** of One Shot to the tank and mix.
3. Fit the DPF to the machine and run the cleaning cycle as normal, following the METclean Lite operating instructions.
4. When the solution is spent, drain the tank into a sealed container and dispose of it through a licensed waste management company.

OPTION B: DIRECT SOAK

1. **Blank off all openings** on the DPF (inlet, outlet and sensor ports) so the unit will hold liquid. Stand it upright on a drip tray.
2. Pour **500ml of One Shot** (half the bottle) into the DPF.
3. Top up the DPF with **clean water** until full.
4. Leave the DPF to soak for **1 hour**.
5. Remove the blanks and drain the solution into a sealed container. **Do not drain into a sink or drain.**
6. **Finish the clean on a METclean machine**, following the machine's operating instructions.
7. Dispose of the drained solution through a licensed waste management company.

Cap the bottle and keep the remaining 500ml for the next DPF.

IMPORTANT

Always fix any vehicle faults before refitting a cleaned DPF, to ensure good results and prevent the filter blocking again.

Never drain used cleaning solution into a sink, drain or watercourse.

FIRST AID

EYES	Rinse immediately with plenty of running water for 10 to 15 minutes, holding the eyelids apart. Remove contact lenses if easy to do. **Get immediate medical advice.**
SKIN	Remove contaminated clothing and wash it before reuse. Wash skin with plenty of water. Get medical advice if irritation occurs.
INHALED	Move to fresh air.
SWALLOWED	Rinse mouth and drink plenty of water. Do not induce vomiting.

STORAGE AND DISPOSAL

Keep the bottle tightly closed and store locked up in a ventilated area, out of reach of children and accessible to authorised persons only.

Never allow the product or used cleaning solution to enter drains, surface water or watercourses. Collect all waste and dispose of it through a licensed waste management company (List of Wastes code 07 07 04, hazardous waste). Fully emptied and rinsed bottles can be recycled.

Read the Safety Data Sheet before use. It is available on request from Mobile Eco Tuning.

METCLEAN

Mobile Eco Tuning
Unit 45, Lynx Crescent, Weston-super-Mare, BS24 9DJ
01934 644427 | info@mobileecotuning.com
www.mobileecotuning.com | UFI: SDSY-C8WA-H00M-7795