MET**CLEAN**

MAINTENANCE TICKLIST · V

KEEP YOUR V CLEAN, WASH AFTER WASH

Two-stage filtration: the tank suction filter and the 50 micron bag (sock) filter in its housing. No stainless filters. The V runs on water alone. Service it at base, never at the roadside. Print the tick sheets as often as you need.

YOUR MACHINE

METClean V

SERIAL NUMBER _____ SITE _____ INSTALLED _____

YOUR SCHEDULE

Counted in cleans. MET's service schedule is a guide: it depends on how dirty the filters you clean are.

ITEM	WHEN	WHAT TO DO
Sock filter	**Every 30 cleans**	Replace the bag (sock) filter. Carry a spare. Sooner after any oily DPF.
Water and ash	**Every 60 cleans**	At base: drain the tank, clean out the ash, fit a new sock, refill.
Soot and ash	**When cleaned out**	Dispose of through a licensed waste carrier.

ISOLATE FIRST

Disconnect from the mains (and air, where used), lock off the supply and remove anything attached before you drain, open or clean anything. Gloves, safety glasses and protective footwear.

OIL CHANGES EVERYTHING

The filtration is not designed for oil. Oil clogs the bag and makes it burst at the bottom, letting dirt through. After any oily DPF, change the bag straight away and change the water sooner. The more oil, the sooner.

STOP AND CALL US

Damaged electrical equipment, a leak you can't trace to a loose connection, a heater that keeps tripping, or a fault that comes back after you've cleared it. Have the model, serial number, what the machine was doing and a photo or video ready.

TICK SHEET · DAILY

DAILY CHECKS

METClean V. A few minutes before you set off. Anything that fails: don't run the machine, report it, and call us if you can't fix it.

WEEK STARTING _____ SERIAL NUMBER _____ CHECKED BY _____

BEFORE SETTING OFF	MON	TUE	WED	THU	FRI	SAT
240 V supply with its RCBO; compressor supplying 5 to 8 bar	☐	☐	☐	☐	☐	☐
Air gauge shows at least 5 bar; water tank full	☐	☐	☐	☐	☐	☐
Wash hose and braided hose undamaged; connections tight	☐	☐	☐	☐	☐	☐
Door closes with both hands and locks with the clasp; straps work; emergency stop released	☐	☐	☐	☐	☐	☐
No damaged or worn electrical equipment (report it, don't use it)	☐	☐	☐	☐	☐	☐
Spare sock filter and adaptors on board	☐	☐	☐	☐	☐	☐
Water condition looks normal (cloudy or oily water: plan a change at base)	☐	☐	☐	☐	☐	☐
Somewhere to contain waste water on today's jobs	☐	☐	☐	☐	☐	☐
Cleans today						
Oily DPF today? (Y / N)						
Initials						

METCLEAN

TICK SHEET · EVERY CLEAN

CLEAN TALLY

METClean V. Tick one box per clean. The shaded box is when the job is due; do it, note the date and start a fresh strip. Oily DPF? Change the bag now, whatever the count.

☐ Due

WATER AND ASH · EVERY 60

Water fill 1 · filled on ..... changed on .....

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	**60**

Water fill 2 · filled on ..... changed on .....

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	**60**

SOCK FILTER · EVERY 30

Sock 1 · fitted ..... replaced .....

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
16	17	18	19	20	21	22	23	24	25	26	27	28	29	**30**

Sock 2 · fitted ..... replaced .....

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
16	17	18	19	20	21	22	23	24	25	26	27	28	29	**30**

Sock 3 · fitted ..... replaced .....

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
16	17	18	19	20	21	22	23	24	25	26	27	28	29	**30**

TIP

Plan sock and water changes for days at base. At 60 cleans fit a new sock while the tank is empty.

METCLEAN

TICK SHEET · SERVICE

SERVICE AND WASTE

METClean V. An outline of each job to tick off as you go. Follow the full instructions for your machine, with their safety section, and only after training.

SOCK FILTER CHANGE

- [ ] **At base**
  Power off and isolated; containers ready. Never at the roadside.
- [ ] **Empty the machine water**
  Drain the tank into containers for licensed disposal.
- [ ] **Open the housing**
  Remove the ring of hex caps on the filter housing.
- [ ] **Replace the sock**
  Lift the used sock out over a container; keep it for disposal; fit a new one.
- [ ] **Refit and close**
  Refit the lid and caps without damaging the seal.
- [ ] **Refill**
  Clean water to the correct level; check for leaks before the next job.

DATE _____ CLEAN COUNT _____ INITIALS _____

WATER AND ASH

- [ ] **At base**
  Machine isolated; containers ready.
- [ ] **Drain the tank**
  Drain into containers for licensed disposal.
- [ ] **Clear the ash**
  Clean the ash out of the bottom of the tank; fit a new sock.
- [ ] **Close and refill**
  Close the drain; fill with clean water to the correct level.
- [ ] **Check**
  Run briefly and check for leaks before setting off.
- [ ] **Start a new tally**
  Note the date on a fresh water strip.

DATE _____ CLEAN COUNT _____ INITIALS _____

WASTE RECORD

Sealed, labelled containers until collection. Never to ground, surface water or an ordinary drain. Used water to a licensed waste fluid company; soot, ash and spent filters to a licensed waste carrier. If you carry the waste yourself, check your waste carrier registration with the Environment Agency.

DATE	WASTE	QUANTITY	LICENSED COMPANY OR CARRIER	NOTE OR REFERENCE