METCLEAN

MAINTENANCE TICKLIST · WASHPRO

KEEP YOUR WASHPRO CLEAN, WASH AFTER WASH

A heated parts washer with a detergent bath: a dedicated low-foaming spray-wash detergent (MET specifies Arrow Solutions Aquaklenz CP), a filter on the pump side and an oil skimmer. Print the tick sheets as often as you need.

YOUR MACHINE

METClean WashPRO

SERIAL NUMBER _____ SITE _____ INSTALLED _____

YOUR SCHEDULE

Condition-based, as the operating and safety instructions describe: there is no fixed count.

ITEM	WHEN	WHAT TO DO
Filter	**Regularly, and when spray pressure drops**	Turn the pump, heater and main switch off; remove the filter with the filter tool; wash it out until clean; replace it if worn; refit and purge.
Surface oil	**Every day**	Run the oil skimmer with a container under the outlet; empty the container as waste oil.
Water level	**Every day**	Top up with fresh water only. Add concentrate only when cleaning power drops, or after a full refill.
Wash water	**When it stays dirty after skimming**	Or when cleaning power drops even after adding concentrate: cool, drain, remove sludge, clean the filter, refill.

ISOLATE FIRST
Disconnect from the mains (and air, where used), lock off the supply and remove anything attached before you drain, open or clean anything. Gloves, safety glasses and protective footwear.

CHEMICALS
One dedicated spray-wash detergent at a time; always add chemical to water. Never solvents, petrol, paraffin, thinners or flammable cleaners. Read the detergent's safety data sheet.

STOP AND CALL US
Damaged electrical equipment, a leak you can't trace to a loose connection, a heater that keeps tripping, or a fault that comes back after you've cleared it. Have the model, serial number, what the machine was doing and a photo or video ready.

TICK SHEET · DAILY

DAILY CHECKS

METClean WashPRO. A few minutes before the first clean of the day. Anything that fails: don't run the machine, report it, and call us if you can't fix it.

WEEK STARTING _____ SERIAL NUMBER _____ CHECKED BY _____

BEFORE THE FIRST CLEAN	MON	TUE	WED	THU	FRI	SAT
Water at full, topped up with fresh water	☐	☐	☐	☐	☐	☐
Oil container in place under the skimmer outlet and not full	☐	☐	☐	☐	☐	☐
Filter clean and housing tight	☐	☐	☐	☐	☐	☐
Door seal clean and undamaged	☐	☐	☐	☐	☐	☐
Cables, plug and hoses free from damage	☐	☐	☐	☐	☐	☐
Viewing window and wiper blade clean	☐	☐	☐	☐	☐	☐
Water at working temperature before using the foot pedal	☐	☐	☐	☐	☐	☐
Parts washed today						
Initials						

TICK SHEET · FILTER AND WATER

FILTER AND WATER LOG

METClean WashPRO. One row per job: tick what you did. Change the water when it stays dirty after skimming, or cleaning power drops even after adding concentrate.

DATE	FILTER CLEANED	FILTER REPLACED	OIL EMPTIED	CONCENTRATE ADDED	WATER CHANGED	INITIALS
	☐	☐	☐	☐	☐	
	☐	☐	☐	☐	☐	
	☐	☐	☐	☐	☐	
	☐	☐	☐	☐	☐	
	☐	☐	☐	☐	☐	
	☐	☐	☐	☐	☐	
	☐	☐	☐	☐	☐	
	☐	☐	☐	☐	☐	
	☐	☐	☐	☐	☐	
	☐	☐	☐	☐	☐	
	☐	☐	☐	☐	☐	
	☐	☐	☐	☐	☐	
	☐	☐	☐	☐	☐	
	☐	☐	☐	☐	☐	
	☐	☐	☐	☐	☐	
	☐	☐	☐	☐	☐	
	☐	☐	☐	☐	☐	
	☐	☐	☐	☐	☐	

TIP

Note anything unusual, such as spray pressure that stays low after cleaning the filter, in the margin for when you call us.

METCLEAN

TICK SHEET · SERVICE

SERVICE AND WASTE

METClean WashPRO. An outline of each job to tick off as you go. Follow the full instructions for your machine, with their safety section, and only after training.

CLEANING THE FILTER

- [ ] **Switch off**
  Pump and heater off, then the main switch.
- [ ] **Remove the filter**
  Undo the filter housing with the filter tool.
- [ ] **Wash it out**
  Clean water until all sludge and debris is gone; check it for damage.
- [ ] **Replace if worn**
  Fit a new filter if it is worn or damaged.
- [ ] **Refit and purge**
  Tighten with the filter tool; switch on, close the door, press the foot pedal to purge air.

DATE _____ DONE _____ INITIALS _____

CHANGING THE WASH WATER

- [ ] **Cool**
  Heater off; let the water cool before draining.
- [ ] **Drain**
  Open the discharge valve into a suitable container.
- [ ] **Clean out**
  Remove the sludge from the bottom of the tank; clean the filter.
- [ ] **Refill**
  Valve closed; two-thirds clean water, add the detergent as the dilution table shows, top up to full.
- [ ] **Heat and purge**
  Heat to working temperature; door closed; foot pedal until the spray runs steadily.

DATE _____ DONE _____ INITIALS _____

WASTE RECORD

Sealed, labelled containers until collection. Never to ground, surface water or an ordinary drain. Used wash water as trade effluent and waste oil through a licensed carrier; check your local water authority guidelines. Sludge and worn filters through your licensed waste route.

DATE	WASTE	QUANTITY	LICENSED COMPANY OR CARRIER	NOTE OR REFERENCE